

Generating daily gap-filled BRDF adjusted surface reflectance products with 10 m resolution using geostationary satellite

Juwon Kong^{a,b}, Youngryel Ryu^{a,b,c}, Sungchan Jeong^{b,c}, Wonseok Choi^{a,b}, Henock Mammo^d

^a Interdisciplinary Program in Landscape Architecture, Seoul National University, Seoul, Republic of Korea
^b Integrated Major in Smart City Global Convergence, Seoul National University, Seoul, Republic of Korea
^c Department of Landscape Architecture and Rural Systems Engineering, Seoul National University, Seoul, Republic of Korea
^d Research Institute of Agriculture and Life Sciences, Seoul National University, Seoul, Republic of Korea

B15I: Data Fusion in Earth Observation Science I Poster

Q. Can we use geostationary satellite products for generating daily surface reflectance products with 10m spatial resolution?

Challenges and Solutions

1) Spatial resolution → **Spatiotemporal image fusion**

2) Angular effect → **BRDF Correction**

Example of usage → **NIRv = NDVI x NIR** (Badgley et al, 2017)

- Normalized Difference Vegetation Index (NDVI) (Tucker 1979)
- Near-infrared reflectance of vegetation (NIRv) (Badgley et al, 2017)
- For GPP estimation, we recommend 'NIRvP' (Dechant et al., 2020,2022; Baldocchi et al., 2019)

Methods

* All the results derived from 2020 datasets.


Image fusion → **SFSDAF v1.0** (Li et al, 2020)

BRDF Correction → **RosThick-LiSparse model**

Satellite products → **Sentinel 2, Landsat 8, MODIS, GK2A**

- Eddy covariance system includes a three-dimensional sonic anemometer (Model CSAT3; Campbell Scientific Inc. Logan, UT, USA) and an enclosed-path infrared gas analyzer (Model LI-7200; LI-COR Inc., Lincoln, NE, USA)
- The flux data were processed by the KoFlux data protocol including quality control, gap-filling and CO₂ flux partitioning (Hong et al. 2009; Kang et al. 2018a; Kang et al. 2018b)
- Hyperspectral system includes hyperspectral sensor (full width at half maximum of 4 nm, Jaz; Ocean Optics, Dunedin, FL, USA) with two optics fibers that equipped with cosine correctors (CC-3; Ocean Optics, Dunedin, FL, USA)

Site



- (a) A map of Korean Peninsula (image source: Google Earth) with the study site, which is registered in Korea Flux Network (KoFlux) as well as Asia Flux Network (AsiaFlux), Cheorwon marked in red arrow.
- (b) The study site image acquired on 5th September 2017, which shows rice paddy fields with different harvest dates boarded with soybean plants

Overall processes and Results with evaluation




Figure 1 Overall process of spatiotemporal image fusion (STIF) after the preprocessing




Figure 2 Evaluation of spatiotemporal image fusion products NDVI and NIRv against in-situ NDVI and NIRv




Figure 3 Examples of STIF-based NIRv maps (July 2019). a) Gap-filling the coarse spatial resolution products. b) STIF step1 using 30m resolution SR products c) STIF step2 using 30m resolution SR products

Discussion & Conclusion

1. What causes the uncertainty of STIF based maps?

- For gap-free surface reflectance product, we conducted two gap-filling process, which double the uncertainty.
- Spatial and temporal resolution difference between coarse and fine resolution products were over 10 times.

2. Can STIF based maps detect the spatial heterogeneity over fields?

- STIF based maps can detect the spatial heterogeneity over fields.
- STIF based maps can track the changes of land surface reflectance.

3. The strength of current STIF based map compared to the other STIF

- When using full BRDF inversion produces, MODIS products cannot monitor land surface during the monsoon season. However, Continuous observations from geostationary satellites have been utilized to understand land surface seasonal dynamics and fill data gaps caused by clouds.
- By utilizing continuous observations from geostationary satellites products into STIF, data gaps caused by clouds can be filled and seasonal dynamics can be understood.

Future study

- We expect that further studies evaluate STIF based map over variety of ecosystem

Answer. YES WE CAN.

For precision agriculture and monitoring seasonal variation of GPP over heterogeneous landscape

Email: Juwon Kong paradigm21@snu.ac.kr / paradigm21c@gmail.com

References

- Badgley, G., Field, C.B., & Berry, J.A. (2017). Canopy near-infrared reflectance and terrestrial photosynthesis. *Science Advances*, 3, e1602244
- Baldocchi, D.D., Ryu, Y., Dechant, B., Eichmann, E., Hemes, K., Ma, S., Sanchez, C.R., Shortt, R., Szara, D., Valach, A., Verfaillie, J., Badgley, G., Zeng, Y., & Berry, J.A. (2020). Outgoing Near-Infrared Radiation From Vegetation Scales With Canopy Photosynthesis Across a Spectrum of Function, Structure, Physiological Capacity, and Weather. *Journal of Geophysical Research: Biogeosciences*, 125, e2019JG005534
- Dechant, B., Ryu, Y., Badgley, G., Zeng, Y., Berry, J.A., Zhang, Y., Li, Z., Zhang, Q., Kang, M., Li, J., Moya, I. (2019) Canopy structure explains the relationship between photosynthesis and sun-induced chlorophyll fluorescence in crops. *Remote Sensing of Environment*
- Dechant, B., Ryu, Y., Badgley, G., Köhler, P., Rascher, U., Migliorini, M., Zhang, Y., Tagliabue, G., Guan, K., Rossini, M., Goulas, Y., Zeng, Y., Frankenberg, C., & Berry, J.A. (2022). NIRvP: A robust structural proxy for sun-induced chlorophyll fluorescence and photosynthesis across scales. *Remote Sensing of Environment*, 268, 112763
- Hong, J., Kwon, H.-J., Lim, J.-H., Byun, Y.-H., Lee, J.-H., & Kim, J. (2009). Standardization of KoFlux Eddy-Covariance Data Processing. *Korean Journal of Agricultural and Forest Meteorology*, 11

Kang, M., Kim, J., Lee, S.-H., Kim, J., Chun, J., & Cho, S. (2018a). Changes and Improvements of the Standardized Eddy Covariance Data Processing in KoFlux, 5-17

Kang, M., Kim, J., Malla Thakuri, B., Chun, J., & Cho, S. (2018b). New gap-filling and partitioning technique for H2O eddy fluxes measured over forests. *Biogeosciences*, 15, 631-647

Kijun, N., Calanca, P., Rotach, M.W., & Schmid, H.P. (2015). A simple two-dimensional parameterisation for Flux Footprint Prediction (FFP). *Geosci. Model Dev.*, 8, 3695-3713

Tucker, C.J. (1979). Red and photographic infrared linear combinations for monitoring vegetation. *Remote Sensing of Environment*, 8, 127-150

This study was carried out with the support of Korea Forest Service (Project #202018B10-2022-BB01)